



## Perfiles normalizados ÁNGULO LADOS DESIGUALES



| Código           | a<br>mm | b<br>mm | c<br>mm | Aleación     | M Ix<br>cm <sup>4</sup> | M Iy<br>cm <sup>4</sup> | W x<br>cm <sup>3</sup> | W y<br>cm <sup>3</sup> |
|------------------|---------|---------|---------|--------------|-------------------------|-------------------------|------------------------|------------------------|
| 1.02.220         | 20      | 10      | 1,5     | 6060/6063-T5 | 0,030                   | 0,177                   | 0,039                  | 0,138                  |
| 1.02.270         | 25      | 10      | 2,0     | 6060/6063-T5 | 0,039                   | 0,421                   | 0,050                  | 0,275                  |
| 1.02.300         | 30      | 15      | 1,5     | 6060/6063-T5 | 0,109                   | 0,621                   | 0,092                  | 0,320                  |
| 1.02.320         | 30      | 20      | 2,0     | 6060/6063-T5 | 0,322                   | 0,891                   | 0,211                  | 0,440                  |
| 1.02.340         | 35      | 10      | 1,2     | 6060/6063-T5 | 0,028                   | 0,670                   | 0,033                  | 0,321                  |
| 1.02.360         | 35      | 15      | 1,5     | 6060/6063-T5 | 0,113                   | 0,946                   | 0,093                  | 0,427                  |
| 1.02.400         | 40      | 20      | 1,5     | 6060/6063-T5 | 0,313                   | 1,698                   | 0,195                  | 0,651                  |
| 1.02.410         | 40      | 20      | 2,0     | 6060/6063-T5 | 0,347                   | 1,963                   | 0,218                  | 0,758                  |
| 1.02.430         | 40      | 25      | 2,0     | 6060/6063-T5 | 0,662                   | 2,123                   | 0,340                  | 0,788                  |
| 1.02.450         | 40      | 30      | 2,0     | 6060/6063-T5 | 1,110                   | 2,258                   | 0,486                  | 0,811                  |
| 1.02.520         | 50      | 25      | 1,8     | 6060/6063-T5 | 0,636                   | 3,533                   | 0,316                  | 1,083                  |
| 1.02.540         | 50      | 30      | 2,0     | 6060/6063-T5 | 1,174                   | 4,151                   | 0,497                  | 1,235                  |
| 1.02.590         | 52      | 17      | 2,0     | 6060/6063-T5 | 0,228                   | 3,800                   | 0,162                  | 1,203                  |
| 1.02.600         | 60      | 15      | 2,0     | 6060/6063-T5 | 0,161                   | 5,398                   | 0,127                  | 1,535                  |
| 1.02.630         | 60      | 32      | 2,0     | 6060/6063-T5 | 1,488                   | 6,971                   | 0,580                  | 1,757                  |
| 21.82.006.640.02 | 60      | 40      | 4,0     | 6082-T6      | 5,187                   | 14,275                  | 1,701                  | 3,525                  |
| 1.02.700         | 70      | 35      | 2,0     | 6060/6063-T5 | 1,977                   | 10,904                  | 0,696                  | 2,376                  |
| 1.02.760         | 80      | 40      | 2,0     | 6060/6063-T5 | 3,018                   | 16,392                  | 0,927                  | 3,119                  |
| 1.02.770         | 85      | 25      | 1,7     | 6060/6063-T5 | 0,818                   | 14,138                  | 0,381                  | 2,747                  |
| 1.02.800         | 100     | 50      | 6,0     | 6060/6063-T5 | 15,724                  | 90,491                  | 3,995                  | 14,060                 |
| 21.82.006.800.02 | 100     | 50      | 6,0     | 6082-T6      | 15,724                  | 90,491                  | 3,995                  | 14,060                 |
| 21.05.004.800.02 | 100     | 50      | 6,0     | 6005-T4      | 15,724                  | 90,491                  | 3,995                  | 14,060                 |
| 1.02.820         | 103     | 36      | 2,0     | 6060/6063-T5 | 2,318                   | 31,252                  | 0,759                  | 4,881                  |
| 1.02.850         | 110     | 30      | 2,0     | 6060/6063-T5 | 1,685                   | 35,285                  | 0,649                  | 5,350                  |
| 1.02.900         | 150     | 90      | 9,5     | 6060/6063-T5 | 142,110                 | 512,742                 | 20,437                 | 51,514                 |
| 21.82.006.910.02 | 150     | 100     | 10,0    | 6082-T6      | 202,625                 | 557,625                 | 26,573                 | 55,074                 |