




## Perfiles normalizados TUBO REDONDO



Código	D mm	d mm	a mm	Aleación	M Ix cm <sup>4</sup>	W x cm <sup>3</sup>
1.08.180	12,0	10,0	1,00	6060/6063-T5	0,053	0,088
1.08.195	13,0	10,5	1,25	6060/6063-T5	0,081	0,124
1.08.225	16,0	13,0	1,50	6060/6063-T5	0,182	0,227
1.08.235	18,0	15,0	1,50	6060/6063-T5	0,267	0,296
1.08.260	20,0	17,0	1,50	6060/6063-T5	0,375	0,375
1.08.285	22,0	19,0	1,50	6060/6063-T5	0,510	0,464
1.08.310	25,0	21,0	2,00	6060/6063-T5	0,963	0,770
1.08.315	25,0	22,0	1,50	6060/6063-T5	0,768	0,614
1.08.340	26,0	16,5	4,75	6060/6063-T5	1,879	1,446
21.82.006.340.08	25,6	16,5	4,55	6082-T6	1,744	1,363
1.08.345	26,0	22,0	2,00	6060/6063-T5	1,093	0,841
1.08.370	30,0	20,0	5,00	6060/6063-T5	3,191	2,127
1.08.380	30,0	24,0	3,00	6060/6063-T5	2,347	1,565
21.82.006.380.08	30,0	24,0	3,00	6082-T6	2,347	1,565
1.08.385	30,0	25,0	2,50	6060/6063-T5	2,059	1,373
1.08.390	30,0	26,0	2,00	6060/6063-T5	1,733	1,155
1.08.395	30,0	27,0	1,50	6060/6063-T5	1,367	0,912
1.08.410	32,0	29,0	1,50	6060/6063-T5	1,675	1,047
1.08.425	33,0	28,0	2,50	6060/6063-T5	2,804	1,699
1.08.445	35,0	30,0	2,50	6060/6063-T5	3,390	1,937
1.08.450	35,0	31,0	2,00	6060/6063-T5	2,833	1,619
1.08.480	40,0	30,0	5,00	6060/6063-T5	8,590	4,295
21.82.006.480.08	40,0	30,0	5,00	6082-T6	8,590	4,295
1.08.495	40,0	35,0	2,50	6060/6063-T5	5,200	2,600
21.82.006.495.08	40,0	35,0	2,50	6082-T6	5,200	2,600
1.08.500	40,0	36,0	2,00	6060/6063-T5	4,322	2,161
1.08.545	45,0	40,0	2,50	6060/6063-T5	7,563	3,361
21.82.006.545.08	45,0	40,0	2,50	6082-T6	7,563	3,361
1.08.550	45,0	41,0	2,00	6060/6063-T5	6,258	2,781
1.08.560	48,0	42,0	3,00	6060/6063-T5	10,783	4,493
21.82.006.560.08	48,0	42,0	3,00	6082-T6	10,783	4,493
1.08.565	50,0	40,0	5,00	6060/6063-T5	18,113	7,245
21.82.006.565.08	50,0	40,0	5,00	6082-T6	18,113	7,245
1.08.570	50,0	45,0	2,50	6060/6063-T5	10,551	4,220
21.82.006.570.08	50,0	45,0	2,50	6082-T6	10,551	4,220
1.08.575	50,0	46,0	2,00	6060/6063-T5	8,701	3,480
1.08.580	50,0	47,0	1,50	6060/6063-T5	6,727	2,691
1.08.589	55,0	52,0	1,50	6060/6063-T5	9,027	3,283
1.08.590	55,0	50,0	2,50	6060/6063-T5	14,238	5,178
1.08.595	60,0	50,0	5,00	6060/6063-T5	32,938	10,979
21.82.006.595.08	60,0	50,0	5,00	6082-T6	32,938	10,979

M Ix: momento de inercia respecto al eje x. W x: módulo de flexión respecto al eje x.


• Acabados: bruto de fabricación, anodizados y lacados.

• Longitud de suministro: 6.000 mm

\* Bajo pedido se pueden suministrar longitudes diferentes de la estándar y/o cortados a medida.



## Perfiles normalizados TUBO REDONDO



Código	D mm	d mm	a mm	Aleación	M Ix cm <sup>4</sup>	W x cm <sup>3</sup>
1.08.610	60	55,0	2,5	6060/6063-T5	18,699	6,233
21.82.006.610.08	60	55,0	2,5	6082-T6	18,699	6,233
1.08.615	60	57,0	1,5	6060/6063-T5	11,801	3,934
1.08.640	65	60,0	2,5	6060/6063-T5	24,007	7,387
1.08.642	65	62,6	1,2	6060/6063-T5	12,242	3,767
1.08.654	70	60,0	5,0	6060/6063-T5	54,242	15,498
1.08.660	70	65,0	2,5	6060/6063-T5	30,235	8,639
1.08.670	75	70,0	2,5	6060/6063-T5	37,457	9,988
1.08.675	80	70,0	5,0	6060/6063-T5	83,203	20,801
21.82.006.675.08	80	70,0	5,0	6082-T6	83,203	20,801
1.08.685	80	75,0	2,5	6060/6063-T5	45,746	11,437
21.82.006.685.08	80	75,0	2,5	6082-T6	45,746	11,437
1.08.705	90	80,0	5,0	6060/6063-T5	121,000	26,889
21.82.006.705.08	90	80,0	5,0	6082-T6	121,000	26,889
1.08.715	100	80,0	10,0	6060/6063-T5	289,812	57,962
1.08.725	100	90,0	5,0	6060/6063-T5	168,812	33,762
21.82.006.725.08	100	90,0	5,0	6082-T6	168,812	33,762
1.08.745	110	100,0	5,0	6060/6063-T5	227,815	41,421
1.08.760	120	106,0	7,0	6060/6063-T5	398,159	66,360
21.82.006.765.08	120	110,0	5,0	6082-T6	299,188	49,865
21.82.006.778.08	130	120,0	5,0	6082-T6	384,109	59,094
1.08.813	150	140,0	5,0	6060/6063-T5	599,308	79,908
1.08.825	160	150,0	5,0	6060/6063-T5	731,942	91,493

M Ix: momento de inercia respecto al eje x.      W x: módulo de flexión respecto al eje x.

• **Acabados:** bruto de fabricación, anodizados y lacados.

• **Longitud de suministro:** 6.000 mm

\* Bajo pedido se pueden suministrar longitudes diferentes de la estándar y/o cortados a medida.